

RG5967-40Q

RG5967-40Q, Quad-Shield Cable



Material Specification

Inner Conductor	21% Copper-Clad Steel	0.81±0.02 mm
Dielectric	Foam PE	3.66±0.10 mm
Aluminum Foil	Bonded APA	3.86±0.13 mm
Braid	67% Braid Al-Mg	80*0.12 mm
Aluminum Foil	APA	4.51±0.20 mm
Braid	40% Braid Al-Mg	48*0.12 mm
Jacket	Black / White PVC	6.73±0.20 mm

Electrical And Mechanical Specification

Characteristic Impedance	75±3 Ω	
Velocity of Propagation	82%	
Capacitance	52.3 PF/m	
Insulation Resistance,min	5000 MΩ*km	
Jacket Spark Test Voltage	3 KV	
RL min	5-1002 MHz	23 dB
	1002-1218 MHz	20 dB
	1218-1794 MHz	19 dB
	1794-2250 MHz	18 dB
	2250-3000 MHz	16 dB

Environmental Specifications

Installation Temperature	-25°C~+70°C
Operating Temperature	-25°C~+70°C
Storage Temperature	-25°C~+70°C
RoHS 2011/65/EU	Compliant

Attenuation @ 20°C max

Frequency, MHz	dB/100ft	dB/100m	Frequency, MHz	dB/100ft	dB/100m
55	2.05	6.73	1350	9.47	31.07
211	3.80	12.47	1410	9.68	31.76
250	4.10	13.45	1450	9.82	32.25
270	4.22	13.85	1602	10.43	34.22
300	4.45	14.60	1675	10.59	34.74
330	4.66	15.29	1700	10.79	35.31
350	4.80	15.75	1794	11.06	36.32
400	5.10	16.73	1800	11.08	36.41
450	5.40	17.72	2000	11.67	38.54
500	5.70	18.70	2200	12.24	40.16
550	5.95	19.52	2400	12.78	41.92
600	6.20	20.34	2550	13.08	42.91
750	6.97	22.87	2700	13.56	44.48
870	7.57	24.85	2800	13.81	45.28
1002	8.12	26.64	2900	14.05	46.10
1218	8.99	29.56	3000	14.30	46.90
1250	9.11	29.89			