

### 3/8" S

3/8" S PE | HCAHY-50-7, Black PE Jacket

3/8" S LSZH | HCAHYZ-50-7, Black LSZH Jacket



#### Material Specification

Inner Conductor	Copper Clad Aluminum	2.60±0.05 mm
Dielectric	Foam Polyethylene	6.90±0.15 mm
Outer Conductor	Helical Corrugated Copper Tube	9.10±0.20 mm
Jacket	LSZH	10.20±0.25 mm
	PE	
Jacket Thickness ,min	—	0.40 mm

#### Electrical Specification

Characteristic Impedance	50 Ω	
Velocity of Propagation	81%	
Capacitance	82.0 pF/m	
Insulation Resistance,min	5000 MΩ•km	
Jacket Spark Test Voltage	3 KV	
RF Peak Voltage	1.04 KV	
Peak Power Rating	12.0 KW	
Cut-off Frequency	13.40 GHz	
PIM (2*43dBm),Typ	-160 dBc (900MHz&1800MHz)	
VSWR max	700-960 MHz	1.13
	1700-2200 MHz	1.15
	2200-2700 MHz	1.18
	3300-3800 MHz	1.20

#### Mechanical Specifications

Single Bending Radius	30 mm
Repeated Bending Radius	60 mm
Bending Numbers	15

#### Environmental Specifications

	PE	LSZH
Storage Temperature	-55°C~+85°C	-30°C~+80°C
Installation Temperature	-40°C~+60°C	-20°C~+60°C
Operating Temperature	-55°C~+85°C	-30°C~+80°C
RoHS 2011/65/EU	Compliant	

#### Attenuation @ 20°C And Average Power Rating @ 40°C

Frequency, MHz	dB/100m	kw	Frequency, MHz	dB/100m	kw
100	4.25	1.90	1800	19.25	0.42
150	5.01	1.60	2000	20.38	0.39
200	6.03	1.30	2200	21.49	0.37
280	7.07	1.11	2400	22.58	0.36
450	9.21	0.87	2500	23.07	0.35
800	12.39	0.64	3000	25.28	0.31
900	13.23	0.60	3300	26.95	0.29
1000	13.92	0.57	3600	28.30	0.27
1500	17.43	0.45	3800	30.05	0.26

The attenuation is typical value, Maximum value shall be 108% of the typical value.